

ATTESTATION of conformity with Low Voltage Directive

Attestation Number:

1488AP0506N039002

Product:

Grid connected photovoltaic inverter

Brand Name:

N/A

Model:

InfiniSolar 10k

Applicant

VOLTRONIC POWER TECHNOLOGY CORP.

Address:

5F, No. 151, Xinhu 1st Road, Neihu District, Taipei, Taiwan,

R.O.C.

Technical Characteristics:

See Next page

The submitted sample of the above equipment has been tested for CE marking according to following European Directive and standards:

- Low Voltage Directive 2006/95/EC

Standards	Report Number	Report date
IEC/EN 62109-2:2011 in conjunction	LD140506N039-R1	2014-11-19
with IEC/EN 62109-1:2010		
With IEC 62040-1:2008 (1st Edition)		
deviation		

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive.

This verification does not imply assessment of the production of the product. The CE marking may be affixed if all relevant and effective European Directives with CE are applicable.

CE

Manager Safety Department

Name: Sam Chou Date: November 19, 2014

This document shall not be reproduced, except in full, without the written approval of Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch.

Information given in this document is related to the tested specimen of the described electrical sample.

Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



Technical Characteristics:

Test item description:	Hybird Grid-tied photovoltaic inverter	
Trademark:	N/A	
Model / Type:	InfiniSolar 10k	
Ratings:	See below	
PV MPP Array Input DC voltage range [V]	400-800	
PV Array Input DC voltage range [V]:	300-900	
PV Array Input AC current [A]:	2x18.6	
Battery Input DC voltage range [V] . [Discharge]	42-56	
Battery Input AC current [A] [Discharge]	275	
Output AC voltage [V]	3/N/PE, 230/400, 50Hz	
Output AC current [A]:	14.5 per phase	
Output power [kW]:	10	
Output DC voltage [V]:	42-56	
Output DC current [A]	200	

Email: customerservice.dg@cn.bureauveritas.com